ETM-90HD TUBE/PIPE BENDER

99 Bending Programs - Auto Cycle

All Steel Construction

Heavier than other makes of tube benders for maximum versatility and safety. **NO Cast frame components!**

Adjustable Bend Angle Preset By means of PLC push button control with memory

Manual - Automatic: Auto function allows automatic bend & return with one command, programmable dwell time after bend/before return to allow part extraction

Bends up to 180° in one Step Quick Change Tooling
Wide Range of Bending Radii:
From 2.5" to 19" as tooling types permit

Standard Accessories:

Service tools, main arbor, instruction manual (tooling optional)



CARELL







SPECIFICATIONS:

Cycle Speed	3.5 seconds /90 no load
Max. Bend Angle	180 degrees + spring back
Speed Reduction	Oil Bath with solid stock gears
Motor Power	4.5 H.P. Self Braking TEFC 3 Phase220V*
Weight	1,200 LBS without tooling

Machine Requires 220V Three Phase Power - To Run on single phase requires an ample sized Rotary Phase Converter at least with 10HP Rating Hard Starting load.

MAXIMUM BENDING CAPACITY

Pipe	3"Sch. 40 or up to 2-1/2" Sch. 80 Pipe
Tube	3.5" x 0.216"
Round Bar	2"
Square Tube	2½" x 2½"



www.carellcorp.com

TEL: 251-937-0948 • FAX: 251-937-0957 P.O. Box 850 Stapleton, AL 36578 Rev 07.28.2021