ETM-I2OHD TUBE/PIPE BENDER 99 Bending Programs - Auto Cycle

All Steel Construction

Heavier than other makes of tube benders for maximum versatility and safety. NO Cast frame components!

Adjustable Bend Angle Preset By means of PLC push button control with memory

Manual - Automatic: Auto function allows automatic bend & return with one command. programmable dwell time after bend/before return

to allow part extraction

Bends up to 180° in one Step Quick Change Tooling Wide Range of Bending Radii: From 2.5" to 19" as tooling types permit

> TAB. 1 > TAB.

Standard Accessories:

ETM Se

Service tools, main arbor, instruction manual (tooling optional)



CARELL

SPECIFICATIONS:

Cycle Speed	15 seconds /180° no load
Max. Bend Angle	180 degrees + spring back
Speed Reduction	Oil Bath with solid stock gears
Motor Power	4.5 H.P. Self Braking TEFC 3 Phase 220V*
Weight	2,315 LBS without tooling

1 2 3

4 5 6

7 8 9 E 0 C

60

Machine Requires 220V Three Phase Power - To Run on single phase requires an ample sized Rotary Phase Converter at least with 10HP Rating Hard Starting load.

MAXIMUM BENDING CAPACITY

REEN

Pipe	4"Sch. 40
Tube	5½″O.D. x 0.216″ wall
Round Bar	3″
Square Tube	4¼" x 4¼"



TEL: 251-937-0948 • FAX: 251-937-0957 P.O. Box 850 Stapleton, AL 36578 Rev 04.20.2022